



Product Datasheet

Part Code: 10-400-003-00

Covert Pinhole Camera

Key Features

- 1/3" Sony Super HAD II CCD
- 600TV Lines
- 0.0002Lux at F1.2 (Sens-up x256)
- 3.6MM Fixed Pinhole Lens
- IP66 Quick-Fit Snap Lock Connector System
- Easy to fix as covert cab camera for driver protection
- Vehicle loom pigtail (included)



Specifications

Description	NTSC	PAL
Image Sensor	1/3" Sony Super HAD II CCD	
Effective Pixels	768(H) x 494(V)	752(H) x 582(V)
Scanning System	2:1 Interlace	
Horizontal Resolution	600TV Lines	
Video Output	CVBS : 1.0Vp-p, 75Ω composite	
S/N (Y Signal)	50dB (AGC off)	
Min. Illumination	0.0002Lux at F1.2 (Sens-up x256)	
Lens	Pinhole 3.6mm Fixed Lens	
Electronic Shutter	Auto (1/60~1/10,000sec)	Auto (1/50~1/10,000sec)
Backlight Compensation	AUTO	
White Balance	ATW	
Day&Night	AUTO	
Input Voltage	DC 12V(±10%)	
Power Consumption	150mA(MAX)	
Operating Temp. / Hum.	-10°C ~ +50°C / MAX 90% RH	
Storage Temp. / Hum.	-20°C ~ +60°C / MAX 90% RH	