



Product Datasheet

Part Code: 10-400-004-00

5MP 360° - Fisheye IP Camera

Key Features

- 185° Fisheye Lens
- 10 Preset positions and 10 Privacy zones
- Alarm in / out
- Ultra High image quality
- Vandal resistant die-cast housing (PanoCam360B)
- MJPEG, MPEG4, H.264 streaming
- 12.5 Frames Per Second
- 5 Watt PoE or 12Vdc
- Indoor, Outdoor, Surface or Flushmount housing options
- Low profile housing option available for transport applications



Specifications

Camera Module	Image Sensor	½.5" CMOS 5MP
	Lens	F2.0 185° Fisheye
	Responsivity	1.4 V/lux-sec
	Max Resolution	2144x1944
	Preset Positions	10
	Privacy Zones	10
	VMD Zones	10
Video	Compression	MJPEG, MPEG-4, H.264
	Frame-rate	12.5fps at Max Res
	Streaming	Multiple simultaneous ePTZ and Panoramic streams
	Bit Rate Control	CBR/VBR bandwidth and frame rate control per stream
System Integration	Application	Open HTTP API for
	Programming Interface	integration with NVR and VMS systems
	Playback Software Developers Kit	SDK for ePTZ and panoramic view creation in NVR playback software
	Alarms	1 x Alarm Input, 1 x Alarm Output
	Alarm triggers	External input
	Alarm events	File upload via FTP, external output activation, TCP output message
General	Temperature Range	0 to +55C
	Power	PoE IEEE 802.3af Class 2 or 12V DC, Max 5W
	Weight	650 grams
	Approvals	CE EN55022, CISPR 22 Class B, EN50130-4 FCC Part 15 subpart B, ANSI C63.4 Class B
	Size	147.5mm diameter - 54mm height