

+44 (0) 1908 690090

Vidiwave Limited Knowlhill, Milton Keynes. MK5 8HL

Product Datasheet

Part Code: 10-400-004-00

2MP 360° - Fisheye IP Camera

Key Features

- H.264 Full Frame at HD1080p
- Video Compression: H.264, MJPEG
- Dual Stream
- Ultra High Image Quality
- Two-way Audio with G.711
- Analytics (People Counting, Smoke/Fire Detection)
- Burnt-in Text, Video Motion Detection Support
- microSD memory card slot for local recording
- Remote Firmware Upgrade over Network
- SMTF
- IP54

Spec

 SMTP Server built in for smart diagnostics IP54 Housing 		
Specifications		
Camera Module	Image Sensor	1/2.7" 1080p CMOS
	Effective Pixels	1920 x 1080
	Scanning System	Progressive Scan
	AGC Control	Auto
	Minimum Illumination	Color : 0.5 lux, BW : 0.001 lux(Sens-up 32X)
	Lens	1.2mm F2.0 2Megapixel
	Field of View	Horizontal 180° Vertical 160°
	Day&Night	Software
Audio	Input	1 channel
	Output	1 channel
	Compression Format	G.711
Function	Digital Input	1
	Digital Output	1
	Network	10/100 Base-T
	Protocol	HTTP, QoS Layer 3 DiffServ, TCP/IP, UDP/IP, RTSP, RTCP, RTP/ UDP, RTP/TCP, mDNS, UPnP, SMTP, DHCP, DNS, DDNS, NTP, SNMPv1/v2c/v3(MIB-II), IGMP, ICMP
	SD Memory	Built-in Micro SD slot(SD card not included)
	(micro SD)	(Recommend Class 4 and higher for HD recordings)
Electrical	Power Source	12V DC
	Power over Ethernet	Support (IEEE 802.3af)
	Power Consumption (Approx)	500 mA @ 12V DC
Video Content Analysis (Included as Standard)	High Performance	Advanced Tracking Algorithm, Low False Alarm Rate
	Easy to Use	Intuitive Web Browser Interface
	Detection Zones	Multi-segment Polygons and Lines
	On-screen Display	Real-time Display of Tracking Data and Events
	Tamper Detection	Detect camera tampering
Mechanical	Material	Polycarbonate
	Colour	lvory
	Dimension	144(Ø), 62.9(H)mm (Without FMB) 168.7(Ø), 64.9(H)mm (With FMB)

360 g



Weight (Approx)