



Product Datasheet

Part Code: 10-130-003-00

Vidistor HD-SDI Hybrid

Realtime 10 Channel H.264 Digital Video Recorder

Key Features

- Removable DVR / HDD Dock
- 2-CH HD, 8-CH Analogue, realtime H.264 DVR with hexaplex operation – record, live, playback, backup, control, & remote access
- H.264 High Profile video compression/decompression with configurable quality
- Max record capabilities – HD: 720p 60/50, 1080p 60/50, Full-D1: 240/200
- Max playback capabilities – HD: 720p 60/50, 1080p 35, Full-D1: 240/200
- Realtime live display for each channel
- Two-way audio capabilities
- Smart search & playback
- Playback rate up to 240/200 IPS
- Audio in * 12 / audio out * 2
- HDMI * 1, VGA * 1, Main monitor * 1, Call monitor * 1
- Up to 5 SATA HDDs, or 4 SATA HDDs and 1 DVD
- Alarm in * 16 / alarm out * 4, alarm set/unset, panic
- Full rail and automotive type approvals



Specifications

System	O.S.	Embedded Linux 3.0
	Multiplex	Hexaplex operation - simultaneous record, live, playback, backup, control, & remote access
	Certification	FCC, CE, e1, EN-50121 and EN-50155.
Video	Format	HD: HD-SDI, Analog: NTSC/EIA or PAL/CCIR
	Input	HD: 2-CH HD-SDI (SMPTE 292M), BNC, 0.8Vp-p/75ohm, up to 1080p30, 720p60 Analog: 8-CH, BNC, 1Vp-p/75ohm
	Main monitor	HDMI x 1, with resolution up to 1920x1080 (Dock Only)



Product Datasheet

Vidistor HD-SDI Hybrid

Specifications.....continued

Video	Main Monitor	VGA x 1, with resolution up to 1920x1080 (Dock Only)
		M12 x 1, 1Vp-p/75ohm
	Loss detection	Yes
	Motion detection	Yes, with configurable detection area & sensitivity
Audio	Privacy masking	Yes
	Input	HD: 4-CH, BNC, same as Video Inputs
		Analog: 8 CH
	Output	1 Line-out level (up to 2Vrms)
Record	Compression	Video: H.264 High Profile
		Audio: ADPCM
	Max frame rate & resolution	HD: 720p 60/50, 1080p 60/50
		Full-D1: 240/200
	Watermark	Yes
	Mode	Manual/Schedule/Alarm/Motion/Panic
	Pre-record time	0 - 10 seconds
	Post-record time	0 - 60 minutes
Display	Resolution	HDMI/VGA – up to 1920x1080
		NTSC – 720*480, PAL – 720*576
	Split windows	1/4/5/10
	Frame rate	Up to 30/25 IPS per display window
	Digital Zoom	X2, X4
	Sequential switch	User adjustable
Playback	Max frame rate & resolution	HD: 720p 60/50, 1080p 35
		Full-D1: 240/200
	Search	Smart search, Date/time, Camera, Alarm, & Motion
	Operation	Play, Fast Forward, Backward, Pause, Stop, etc.
Storage	HDD	> 1TB Internal + 3TB External
		Failure detection & privacy law supported



Product Datasheet

Vidistor HD-SDI Hybrid

Specifications

Storage	HDD Extension	1 eSATA connector
	Backup	2 USB 2.0 port
		Self playback for backup files
Alarm	Set/unset	1 contact or TTL/CMOS signal, polarity selectable
	Panic	1 contact or TTL/CMOS signal, polarity selectable
	Input	16 contact or TTL/CMOS signal, polarity selectable
	Output	2 Normally Open, 2 Normally Closed relay output
	Buzzer	Yes
	Triggered by	Sensor input, Video loss, & Motion
	Event log	Yes
Network	Ethernet	1 RJ-45 10M/100M/1G bps Ethernet connector
	USB 3G dongle	Supported
	Web	Remote setup, monitoring, backup, alarm notification, & remote software upgrade
		Support Windows 7, Vista, XP, and 2000
		Configurable HTTP/SMTP/FTP/Control/Data port
	DDNS	DDNS server
	E-mail	Alarm notification to stationary or mobile devices
	FTP	Alarm video/audio file storage
	Video	1/4/9/16/25/36/49/64 split-window & SEQ mode for I.E. and HEM
		Dynamic electronics maps for HEM
		N-Streaming live view
	Audio	Two-way
	Protocol	TCP/IP, HTTP, PPPoE, DHCP, DDNS, FTP, TSP
	Remote users	Up to 8 users simultaneously
	Remote	Setup & upload via Windows application software
	Multi-lingual	Yes



Product Datasheet

Vidistor HD-SDI Hybrid

Specifications....continued

	Bandwidth	TCP/IP type dynamic sliding window control
	Remote stations	PC, mobile phone, PDA, and/or tablet PC
		With free iPhone/iPad/Android software app.
Control / GPS / POS	Remote Controller	1 remote controller
		Optional extension cable
	RS-232	1 M12 connector for PTZ, keyboard, POS, or GPS
Setup	RS-485	2-pin for keyboard/PTZ control
	Local	On screen setup via mouse, and/or RS-485 keyboard
	Remote	Setup & upload via Windows application software
Reliability	Multi-lingual	Yes
	System recovery	Auto power on after power loss recovery
	Watch Dog Timer	Yes
Weights & Measures	Timer	Built-in real time clock
	Security	Multi-level password (4 levels, up to 18 accounts)
	Dimension	TBC
Power	Weight	TBC
	Source	10-30 VDC
	Temperature	0°C ~ +40°C
Certifications	Rail	EN50155 / EN50121 / EN61373
	Automotive	2004/108/EC - 95/54EC / EN61373
	Internal PSU	See Vidisafe Compact datasheet for full specification
Dimensions	W x H x D - 380mm x 145mm x 195mm	