



Product Datasheet

Part Code: 10-120-002-00

Vidistor IP66 Rail Pro Extreme

Waterproof Ultra-Rugged Mobile DVR – 4/8 or 16 Channel

Key Features

- H.264 Compression (Main Profile)
- Real-time Recording at CIF quality (all channels)
- Selectable Record Quality & Frame Rate per camera / per mode (normal & alarm): CIF (D1), 2CIF and 4CIF supported.
- Pentaplex Operation: (Supports Live / Record / Play back/ Transmit modes simultaneously)
- Dual Stream – Optimises Network Speeds - 3G/WLAN
- Supports Full management and connectivity - 3G/WLAN
- Supports RS-232 or RS485 data Text Insertion as Meta tag
- Friendly Local Set-Up / Support Interface – USB/Bluetooth /2.4GHz mouse
- S.M.A.R.T (Self Monitoring Analysis & Reporting Technology)
- WCS (Watermark Check System) – Anti-Tamper for admissible to evidence to court
- Waterproof IP66 construction for Rail and Marine Fleet
- Extreme Temperature Range (-40 ~ +75°C)
- Bespoke Internal Climate Control
- Customisable Mil and Rail spec connector panel
- Extreme vibration and temperature certified



Specifications

Software Features	Automatic connection of DVR's for newly coupled vehicles to Driver or Guard's Control Interface
	Up to x 64 camera supported by Driver's Control Interface software
	Supports Multiple Connections to Remote DVR's simultaneously (Live & Playback)
	Remote Setup (full DVR and IP configuration)
	Remote Event search engine for playback
	Remote Time & Date search engine
	Remote GPS and meta data search engine
	2-way Audio (Bi-directional) – to Driver / Passenger areas with local DVR



Product Datasheet

Vidistor IP66 Rail Pro Extreme

Specifications.....continued

Software Features (Continued)	Supports Instant Archiving on demand via 3G and WLAN
	Supports Remote Scheduled archiving of events and user defined time slots.
	Supports multi-user access/function control levels
	Supports automatic emailing of PASCOM alarms with video snapshot image
	Supports automated backup of all alarms to an off-train FTP server via WLAN and 3G
	Supports Automated PUSH diagnostics for DVR and camera health via real-time email alerts.
	Supports GPS fleet tracking to help fleet managers locate last location of remote infrastructure
Hardware	
Customisation Options (Pre-order only)	Choice of IP66 Chassis connectors: Amphenol / AB / Harting (M12) / Binder
	Own Label Branding and Chassis colour choice
	Custom Chassis mounting options
	Removable HDD access door
Certifications	Rail EMC and EMI: EN50121-2-3:2006
	Rail Environmental: EN50155:2007
	Rail Vibration: EN61373
Operating System Embedded Linux	OS Firmware Linux OS in Flash Memory
NTSC/PAL Selectable	Video Input Composite: 4 / 8 / 16
Max Recording Rate at CIF (FPS)	480 (NTSC) / 400 (PAL) / 25 IPS Per Camera
Ethernet	10 / 100 / 1000 Mbps via M12
Network Bandwidth Control	26 kbps - Unlimited
Video Stream	Dual (Record & Transmission)
Alarm Input	2 (TTL) Programmable as NC/NO
Alarm Output	2 (TTL) Programmable as NC/NO
Alarm Input	4 (TTL)
USB Interface	x3 USB (x1 Front Panel, x2 Rear Panel)



Product Datasheet

Vidistor IP66 Rail Pro Extreme

Specifications.....continued

Search	Date/Time, Calendar, Event, Smart Search, GPS, G-Sensor Event
User Interface (Keyboard)	Mouse via M12
Archive File Format	AVI, MPG, DIVX, H264, JPG2000
SMTP Server	YES
Time Server	YES (GPS / TPS)
Auto DST	YES
Recording Quality	Super / High / Standard (D1 / Half D1 / CIF)
Recording Modes	Continuous / Alarm / Motion / Emergency / Scheduled
Pre-Alarm Recording	YES - User Programmable pre and post alarm
Motion Detection	22 x 15 Zones per Camera
Playback Control	x1, x2, x4, x8, x16, x32, x64
PTZ Control	YES - Via RS485 / 422 Serial Port (M12)
Preset Touring	YES (If head supports)
POS / ATM Support	1 + 2 (Optional)
Multi-Language, 3G Communication, S Mobile	YES - (Windows 6.1 or higher) / Android / Blackberry / iPhone *3G partial VPN support
Primary Storage	eSATA HDD (>2TB)
Clip Copy Storage	Built-in Internal DVD-RW, Memory Stick, CF Card supported
Dimensions (W x H x D)	540mm x 120mm x 250mm

Integrated Power Distribution Unit

	Function		Balanced Wide Ranged Supply	
Input Power			20-30VDC	60 Watts
Max Output Current			7A	± 5%
Output Power				
	DVR	Out 1	12V	± 5%
	Camera	Out 2	12V	± 5%
	Camera	Out 3	12V	± 5%



Product Datasheet

Vidistor IP66 Rail Pro Extreme

Integrated Power Distribution Unit....continued

	Function		Protected Device	
Output Power	Camera	Out 4	12V	± 5%
	Camera	Out 5	12V	± 5%
	Camera	Out 6	12V	± 5%
	Camera	Out 7	12V	± 5%
	Camera	Out 8	12V	± 5%
	Camera	Out 9	12V	± 5%
Output Current				
	DVR	Out 1	2,5A	± 5%
	Camera	Out 2	0,2A	± 5%
	Camera	Out 3	0,2A	± 5%
	Camera	Out 4	0,2A	± 5%
	Camera	Out 5	0,2A	± 5%
	Camera	Out 6	0,2A	± 5%
	Camera	Out 7	0,2A	± 5%
	Camera	Out 8	0,2A	± 5%
	Camera	Out 9	0,2A	± 5%
Spike / Load Dump Protection	Input		Yes	33VDC Limiter
Short Circuit Proof	Output		Yes	
Negative Input Power Proof	Input		Yes	
Fuse Type	Output		Resettable PTCs	
LED Indication	Version / S		No	
	Version / L		Yes	Power Health / DVR Health / HDD Health / Camera Health
Delayed Start Up			Yes	
Delayed Turn Off			Yes	